

Air Restriction Monitors



24800
For use in diesel applications



Threaded Mount Gauge
Thread (1/8-27 NPT)
Mounts directly to air cleaner or air induction piping.
Vacuum Indicator (25 in. H2O)
Locking Type
Operating Temperature: -40 to +250°F (-40 to +121°C)
Accuracy: ±10% at red zone
Material: Polycarbonate housing

24801
For use in diesel applications.



Grommet Mount Gauge
Mounts in a rubber grommet directly to the air cleaner housing or air induction piping.
Vacuum Indicator (25 in. H2O)
Locking Type
Operating Temperature: -40 to +250°F (-40 to +121°C)
Accuracy: ±10% at red zone
Material: Polycarbonate housing

24802
For use in diesel applications.



Remote Mount Gauge
Mounts in a convenient location for good visibility. Air cleaner fittings, vacuum hose, and mounting screws are included.
Vacuum Indicator (25 in. H2O)
Locking Type
Operating Temperature: -40 to +250°F (-40 to +121°C)
Accuracy: ±10% at red zone
Material: Polycarbonate housing

24804
For use in diesel applications.



Dash Panel Gauge
Mounts in a panel or dash for convenience of the driver or operator. Air cleaner fittings and vacuum hose included.
Vacuum Indicator (25 in. H2O)
Locking Type
Operating Temperature: -40 to +250°F (-40 to +121°C)
Accuracy: ±10% at red zone
Material: Polycarbonate housing

As a reminder, it has always been, and remains our recommendation that the selection of a replacement filter be conducted using only the most current application information available. In today's cataloging, the electronic resources (i.e. Internet, interactive electronic) would be the most current application information available. For questions or more information, please contact your local WIX District Sales Manager or call Product Information at: US 1.800.949.6698, Mexico +52(844)8661-21-50, Canada 1-800-567-3703.

Air Restriction Monitors



WS10135
For use with gasoline applications.



Grommet Mount Gauge
Mounts in a rubber grommet directly to the air cleaner housing or air induction piping.
Vacuum Indicator (10 in. H2O)
Locking Type
Operating Temperature: -40 to +250°F (-40 to +121°C)
Accuracy: ±10% at red zone
Material: Polycarbonate housing

WS10133
For use with gasoline applications.



Remote Mount Gauge
Mounts in a convenient location for good visibility. Air cleaner fittings, vacuum hose, and mounting screws are included.
Vacuum Indicator (10 in. H2O)
Locking Type
Operating Temperature: -40 to +250°F (-40 to +121°C)
Accuracy: ±10% at red zone
Material: Polycarbonate housing

WIX HDA-100
Senzit



Replacing analog air filter service indicators, Senzit from WIX Filters gives you access to the condition of your air filter anytime, anywhere via your smartphone. Just plug the rugged sensor into the air handler service port and download the Senzit app. In return, you'll receive accurate data that will help you protect and maintain your equipment, saving you time and money.

Senzit has been designed for heavy-duty applications and works with any air filter brand. It's the latest in filtration technology.

<https://www.senzit.io/>

As a reminder, it has always been, and remains our recommendation that the selection of a replacement filter be conducted using only the most current application information available. In today's cataloging, the electronic resources (i.e. Internet, interactive electronic) would be the most current application information available. For questions or more information, please contact your local WIX District Sales Manager or call Product Information at: US 1.800.949.6698, Mexico +52(844)8661-21-50, Canada 1-800-567-3703.