

Replacement Gaskets

Correct gasket type, size and placement is necessary to ensure that a proper seal is formed during filter installation. Typically, the gasket(s) is included with the filter when it ships from the manufacturer. However in some instances, the filter is used on many different applications and it would not be practical to include all gaskets for all applications. Instead the gasket(s) required for the most common applications are included and others are made available separately. As stated earlier, it is critically important that the correct gasket be used when servicing a filter. Always compare the provided gaskets with the one taken out of service to ensure that they are correct matches. If this is not the case, a different gasket may be required for your application. On-line cataloging resources can help you determine which gasket is appropriate for your application.

Lube & Hydraulic Filters 5" OD Multiple Gaskets Available				
Part No.	Packed	Packed	Special	Special
51632	15661	15658		
51746	15386		15661	15859
51756	15415		15661	15658
51758	15758		15661	15658
51759	15415		15661	15658
51860	15415		15661	15658
51861	15661	15415	15658	

For example, WIX part number 51759 ships with a 15415 gasket included. However, gaskets 15661 and 15658 are also available for use with this filter.

Gasket Diameters			
Number	O.D.	I.D.	Thk.
15415 (Packed)	5.14 (131mm)	4.75 (121mm)	0.195 (5mm)
15658	5.055 (128mm)	4.48 (114mm)	0.359 (9mm)
15661	5.03 (128mm)	4.44 (113mm)	0.19 (5mm)



In this particular instance, the gasket that ships with the product (15415) is used on a mounting base that has a narrow groove. Gasket (15661) is intended for an application on which the mounting base has a wider groove. Gasket (15658) fits yet another application for which the base has no groove. In this instance, the gasket (15658) is L-shaped and significantly different from the other two.

Unintended loss of fluid can lead to catastrophic equipment failure. Choosing the correct filter and the right sealing gasket is critical for proper function and protection of your equipment. Always take the time to be certain that you have correctly matched the application to the filter and the filter to the correct gasket.

As a reminder, it has always been, and remains our recommendation that the selection of a replacement filter be conducted using only the most current application information available. In today's cataloging, the electronic resources (i.e. Internet, interactive electronic) would be the most current application information available. For questions or more information, please contact your local WIX District Sales Manager or call Product Information at: US 1.800.949.6698, Mexico +52(844)8661-21-50, Canada 1-800-567-3703.